



Feature

- ✓ 4 Port 10/100/1000Mbps PoE , 2 port 1000Mbps SFP slot;
- ✓ 4 Port support PoE, supports IEEE 802.3af(15.4W),IEEE802.3at PoE (30W);
- ✓ 10/100/1000Mbps Auto-negotiation , auto-MDI-MDI-X;
- ✓ Supports DIN-Rail installation;
- ✓ Transmission data max. Support: 1518 bytes
- ✓ Super lightning protection, IP40 protection;
- ✓ 6KV port Lightning protection;
- ✓ -40℃~+85℃ operating temperature range;
- ✓ 3-Year Warranty;

Specifications

Product Name	4 port 10/100/1000M Industrial PoE Fiber Switch
Product Model	ND2PG-2FX4TX-SFP
Interface	4*10/100/1000Base-T PoE port + 2*1000Mbps SFP slot
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T;IEEE802.3u;100Base-TX/FX; IEEE802.3ab 100Base-T; IEEE802.3z 100Base-X; IEEE802.3x; IEEE802.3af,IEEE802.3at
PoE Specification	PoE Standard: IEEE802.3af/ IEEE802.3at
	PoE ports: 4 port support PoE
	Power Output: Max. 15.4 watts (IEEE 802.3af) / Max. 30 watts (IEEE 802.3at)
	PoE port Auto detect AF/AT devices
	Output Voltage: DC48-57V
	Power Pin Assignment:1/2+;3/6-
Network Media	10BASE-T: Cat3,4,5 UTP(≤100 meter)
	100BASE-TX: Cat5 or later UTP(≤100 meter)
	1000BASE-TX: Cat6 or later UTP(≤100 meter)
Fiber Media	Interface: SC/SFP Multi-mode:2km / Single-mode:20/40/60/80km
Performance Specification	Bandwidth:16Gbps
	Packet Buffer Memory:1M
	10 Mbps Packet Forwarding Rate:14880 pps/port
	100Mbps Packet Forwarding Rate:148800 pps/port
	1000Mbps Packet Forwarding Rate:1488000 pps/port
	MAC Address Table: 8K
Forwarding Mode	Store-and-Forward
Protection	6KV Lightning protection, IP40 protection
LED Indicators	Power: PWR; Link; PoE; Link/Act
Power Supply	Input Power: 48~57VDC (Terminal Block)
	Input Power:2* 48~57VDC(Dual power redundancy backup)
	Working Consumption: <5W
	Connectors: Phoenix terminal
	Overload protection: 20A
	Reverse polarity protection: 30s
	Alarm contact: No
Working Environment	Working temperature: -40~+85℃ ;
	Storage temperature: -45~+85℃
	Relative Humidity: 5%~95 % (no condensation)